

Local Transactions



COMS4113

COMS4113: Fundamentals of Distributed Systems

Instructor: Hubertus Franke

Columbia University

<https://frankeh.github.io/cu-ds1-2026-fall>



Transactions: A Primer

The abstraction, and what it hides

- We now **break from the distributed setting** to introduce **transactions**, a core concept in state management, and to see how they are implemented in a **single-node** system.
- Afterwards we return to the distributed setting and describe how **distributed transactions** are implemented.
- As part of that we will discuss **atomic commitment** and **consensus** protocols.

Why Transactions?

- A key component of any distributed application is a (distributed) **database** that maintains shared state.
- Two challenges of building even a **non-distributed** DB:
 - **Handling failures** — failures are inevitable, and they create the potential for *partial* computations, plus the question of what is correct after restart.
 - **Handling concurrency** — concurrency is vital for performance (I/O is slow, so overlap it with computation), but it creates **races**, so some form of synchronization is needed.

- A **Turing-award-winning** idea.
- An abstraction provided to programmers that **encapsulates a unit of work** against a database.
- Guarantees that the unit of work is executed **atomically** in the face of failures, and is **isolated** from concurrency.

Jim Gray received the 1998 ACM Turing Award for his work on transaction processing; see [Gray-1978] on the closing slide.

Transaction API

Simple, but very powerful:

```
txID = Begin()
```

Starts a transaction. Returns a unique ID for the transaction.

```
outcome = Commit(txID)
```

Attempts to commit. Returns whether the commit succeeded. If it did, **all** operations in the transaction have been applied to the DB; if it did not, **none** of them has.

```
Abort(txID)
```

Cancels all operations of the transaction and erases their effects on the DB. Can be invoked by the programmer **or by the database engine itself**.

By wrapping a set of accesses in a transaction, the database can **hide failures** and **concurrency** under meaningful guarantees.

One such set of guarantees is **ACID**:

A **Atomicity** — Either all operations in the transaction complete successfully (**commit**), or none of them does (**abort**) — regardless of failures.

← hides **failures**

I **Isolation** — A transaction's behaviour is not impacted by the presence of concurrently executing transactions.

← hides **concurrency**

D **Durability** — The effects of committed transactions **survive failures**.

← survives **crashes**

Where is the **C**? Atomicity, isolation and durability are properties the *database* enforces. **Consistency** is the *application's* invariant — the DB has no mechanism for it, which is why this lecture has mechanisms for A, I and D only.

Example: Without Transactions

```
TRANSFER(src, dst, x)
01  src_bal = Read(src)
02  if (src_bal > x):
03      src_bal -= x
04      Write(src_bal, src)
05      dst_bal = Read(dst)
06      dst_bal += x
07      Write(dst_bal, dst)
```

Invocation: TRANSFER(A, B, 50)

```
REPORT_SUM(acc1, acc2)
01  acc1_bal = Read(acc1)
02  acc2_bal = Read(acc2)
03  Print(acc1_bal + acc2_bal)
```

Invocation: REPORT_SUM(A, B)

Without transactions: what could go wrong?

Crash after line 04

Money leaves src and never arrives at dst. The DB is left in a state no correct execution could produce.

REPORT_SUM between 04 and 07

It reads src *after* the debit and dst *before* the credit, and prints a total that is 50 short.

Example: With Transactions



COMS4113

```
TRANSFER(src, dst, x)
00  txID = Begin()
01  src_bal = Read(txID, src)
02  if (src_bal > x):
03      src_bal -= x
04      Write(txID, src_bal, src)
05      dst_bal = Read(txID, dst)
06      dst_bal += x
07      Write(txID, dst_bal, dst)
09      return Commit(txID)
10  Abort(txID)
11  return FALSE
```

```
REPORT_SUM(acc1, acc2)
00  txID = Begin()
01  acc1_bal = Read(txID, acc1)
02  acc2_bal = Read(txID, acc2)
03  Print(acc1_bal + acc2_bal)
04  Commit(txID)
```

The same code, wrapped.

Begin/Commit/Abort tell the DB where the unit of work starts and ends — and that is the whole of what the programmer has to do.

Both hazards are now the **database's** problem. It must make TRANSFER all-or-nothing across a crash, and it must stop REPORT_SUM from observing the half-done state — without being told which lines conflict.

- **Atomicity and durability**

- Operations either all succeed or none do, despite *temporary* failures of the process or machine running the DB (assume the disk itself does not fail). If they succeed, they **persist**.
- Key mechanism is **write-ahead logging**: log enough information about each operation to disk *before* applying it to the database, so that a failure mid-transaction can be undone.

- **Isolation**

- Operations in a transaction all witness the database in a coherent state, independent of other transactions.
- Key mechanism is **locking**: the DB acquires locks on rows read or written and holds them until the end of the transaction.

Two Mechanisms

Named here, developed next

Two Key Mechanisms

Everything ACID asks for is delivered by two mechanisms:

Two-phase locking (2PL)

A **grow-then-shrink** discipline on locks: acquire everything you need, and only then start releasing.

delivers Isolation

Write-ahead logging (WAL)

Record the change in an on-disk **log** *before* applying it, so any partial work can be undone — or redone.

delivers Atomicity + Durability

They are **independent**: locking says nothing about crashes, and logging says nothing about concurrency. A real DB needs both.

Both mechanisms are developed in full later in this lecture — 2PL from the next slide, WAL from the write-ahead logging section.

Two-Phase Locking (2PL)

Isolation, and what it costs

Lock-Based Concurrency Control



COMS4113

TRANSFER(src, dst, x)

```
00 txID = Begin()
01 src_bal = Read(txID, src)
02 if (src_bal > x):
03     src_bal -= x
04     Write(txID, src_bal, src)
05     dst_bal = Read(txID, dst)
06     dst_bal += x
07     Write(txID, dst_bal, dst)
09     return Commit(txID)
10 Abort(txID)
11 return FALSE
```

REPORT_SUM(acc1, acc2)

```
00 txID = Begin()
01 acc1_bal = Read(txID, acc1)
02 acc2_bal = Read(txID, acc2)
03 Print(acc1_bal + acc2_bal)
04 Commit(txID)
```

Questions: what locks to take, when to take them, and how long to keep them?

The next three slides answer the last question by getting it wrong twice. **Option 1** keeps one lock too long, **option 2** releases too early, and **2PL** is what is left.

Option 1: One Global Lock

```
TRANSFER(src, dst, x)
00  txID = Begin()
01  src_bal = Read(txID, src)
02  if (src_bal > x):
03      src_bal -= x
04      Write(txID, src_bal, src)
05      dst_bal = Read(txID, dst)
06      dst_bal += x
07      Write(txID, dst_bal, dst)
09      return Commit(txID)
10  Abort(txID)
11  return FALSE
```

`<- lock(table)`

`<- unlock(table)`

`<- unlock(table)`

```
REPORT_SUM(acc1, acc2)
00  txID = Begin()
01  acc1_bal = Read(txID, acc1)
02  acc2_bal = Read(txID, acc2)
03  Print(acc1_bal + acc2_bal)
04  Commit(txID)
```

REPORT_SUM does the same: `lock(table)` at 00, `unlock(table)` after Commit.

Problem?

Problem: poor performance.

Serializes *all* transactions against that table, even ones that never touch the same rows.

Option 2: Release After Access

```
TRANSFER(src, dst, x)
00  txID = Begin()
01  src_bal = Read(txID, src)
02  if (src_bal > x):
03      src_bal -= x
04      Write(txID, src_bal, src)
05      dst_bal = Read(txID, dst)
06      dst_bal += x
07      Write(txID, dst_bal, dst)
09  return Commit(txID)
10  Abort(txID)
11  return FALSE
```

<- lock(src)

<- unlock(src)

<- lock(dst)

<- unlock(dst)

Problem?

Problem: insufficient isolation.

Another transaction can read *src* *after* the debit and *dst* *before* the credit — the missing-\$50 report from earlier.

REPORT_SUM(src, dst)

the window

Releasing *src* before taking *dst* opens a window in which the database is **visibly** half-updated. Correctness needs the two locks to *overlap*.

Two-Phase Locking (2PL)

```
TRANSFER(src, dst, x)
```

```
00  txID = Begin()
01  src_bal = Read(txID, src)
02  if (src_bal > x):
03      src_bal -= x
04      Write(txID, src_bal, src)
05      dst_bal = Read(txID, dst)
06      dst_bal += x
07      Write(txID, dst_bal, dst)
09  return Commit(txID)
10  Abort(txID)
11  return FALSE
```


<- lock(src)

<- lock(dst)

<- unlock(src, dst)

<- unlock(src, dst)

Locks held



Phase 1 — acquire locks.


Phase 2 — release locks.

You may not acquire *any* lock after releasing one.

Usually implemented by the **database** releasing all locks automatically at the end of `commit()` or `abort()` — so the peak is held to the very end.

Problems?

2PL Can Lead to Deadlocks



tx1 holds foo and wants bar; **tx2** holds bar and wants foo. Neither will ever release, so both wait forever. Nothing is wrong with either transaction — the deadlock is a property of the *pair*, which is why no amount of local checking can prevent it.

- **Option 1:** each transaction acquires all its locks at once.
 - Not always possible — with foreign-key navigation the rows to lock are only determined at runtime, so you cannot name them up front.
- **Option 2:** each transaction acquires its locks in a predefined global order.
 - As before, not always possible, and it forces every developer to know the global order.
- **Typically:** allow deadlocks to happen, then **detect** them and **abort** transactions as needed to break them.

Deadlock Detection and Resolution

Construct a **waits-for graph** of transactions:

Each **vertex** is a running transaction — **T1...T4** below.


An **edge** $T1 \rightarrow T2$ means *T1 is waiting for a lock that T2 holds*.

There is a deadlock **iff** the graph has a **cycle**.

Cycle $T1 \rightarrow T2 \rightarrow T3 \rightarrow T1$ — all three are stuck.

To resolve, the database **unilaterally** calls `Abort()` on one or a few transactions to break the cycle.

Aborting **T2** alone is enough — one victim, chosen to minimise lost work.



To Remember

For concurrency control, a database may decide **on its own** to kill ongoing client transactions.

So **Abort()** is a critical function: it addresses both concurrency-control *and* atomicity problems.

But how exactly do you **Abort()** a transaction that has already written to the database?

Answer: write-ahead logging.

What to Lock: Granularity

2PL says *when* to release locks. It does not say **what** a lock covers:

Table	one lock per table	cheap bookkeeping, no concurrency
Page	one lock per disk page	a compromise; false conflicts between unrelated rows
Row	one lock per tuple	real concurrency, and many more locks to track

Finer locks mean more concurrency and more overhead. Systems therefore **escalate**: start row-level, and switch to a coarser lock once one transaction holds too many.

Also two **modes**, not one: a **shared** lock for readers (many at once) and an **exclusive** lock for writers (one). Option 1's failure was partly that it made readers exclusive.

Write-Ahead Logging (WAL)

Atomicity and durability, from a log

Write-Ahead Logging

In addition to evolving state in RAM and on disk, keep a separate, **on-disk log** of all operations:

transaction **begin** / **commit** / **abort**

all **updates** — $X = X - \$20$

A transaction's operations are **provisional** until the *commit* record is on disk — results are not revealed to other clients in the meantime.

Observation: disk writes of a **single** page or block are atomic — but writes **across** pages may not be.


That is the whole reason the log exists: a **single** atomic write of a commit record can make an **arbitrarily large** set of changes durable at once.

Log Records: begin / commit / abort

LSN	Log Sequence Number — usually implicit: the address of the first byte of the log entry.
prevLSN	LSN of the previous record for this transaction — a linked list threading each transaction's records together.
xID	Which transaction this record belongs to.
type	The operation: begin, commit, abort, update.

The LSN is an **address**, not a counter: it identifies where the record sits in the log, so a page can cheaply record the last LSN that touched it (slide 32).

The prevLSN chain



Each record points back at the same transaction's previous one — this is how undo walks a transaction backwards.

Log Records: updates

An update record needs **everything** required to **undo** and to **redo** the change:

prevLSN + xID + type	
as before	
the update itself	
page ID	which page
offset	where in the page
length	how many bytes

The pair is the key idea.

old-value lets recovery roll a change *back*; **new-value** lets it roll a change *forward*. One record, both directions.

old-value
for undo

new-value
for redo

This is **physical** (byte-level) logging. Logging the *operation* instead — logical logging — is smaller, and slide 31 returns to it.

WAL: A Worked Example

```
→ xId = begin(); // xId <- 42
→ src.bal -= 20;
→ dest.bal += 20;
→ commit(xId);
```

Disk:

11
src.bal: 100

14
dest.bal: 3

Page cache:

11
src.bal: 80

14
dest.bal: 23

*non-log pages may
stay in memory*

Transaction table:

42: prevLSN = 780

Dirty page table:

11: firstLSN = 860, lastLSN = 860

14: firstLSN = 902, lastLSN = 902

**must flush the
log to disk!**

Log:

780
prevLSN: 0
xId: 42
type: begin

:


860
prevLSN: 780
xId: 42
type: update
page/off/len: 11 / 10 / 4
old-val: 100
new-val: 80

902
prevLSN: 860
xId: 42
type: update
page/off/len: 14 / 10 / 4
old-val: 3
new-val: 23

960
prevLSN: 902
xId: 42
type: commit

The Tail of the Log

The **tail** of the log can be kept in memory until a transaction commits — or until a buffer page is flushed to disk.



Batching the tail is why many transactions can share one disk flush — **group commit**.

Recovering From a Crash

e.g. a system crash. For now, assume the log itself is readable.

1	Analyze	Scan the log forward to rebuild the transaction table and the dirty page table: who was running, what was dirty.	<i>which transactions won, which lost</i>
2	Redo	Replay updates forward , using new-value — for <i>all</i> transactions, not just committed ones.	<i>repeating history</i>
3	Undo	Roll back uncommitted transactions backward , using old-value , following each prevLSN chain.	<i>losers are erased</i>

After all three passes the database is exactly as if every committed transaction had run and no uncommitted one ever started.

Why Redo All Operations?

Redo replays **even the losers** — transactions that never committed and are about to be undone anyway. Why bother?

Interaction with concurrency control

Undo needs the database in the **exact state** the log describes. Replaying everything first restores that state, so undo can then walk backwards through a history it recognises.

It generalizes to logical operations

Any operation with an undo and a redo can be logged — not just byte ranges. Logical logging can be far **smaller and faster** than byte-level.

Repeating history is the trick: restore the past exactly, *then* correct it. Trying to be clever and skip the losers is where recovery bugs live.

The Performance of WAL

Objection: must we write the disk **twice**?

Not always. The data page write is *deferred* and may be batched with others, or coalesced away entirely if the page is updated again before it is flushed.

For byte-level update records you must also **know the old value** — so an update may require a read first.

Writing the log is sequential.

One append-only stream instead of scattered random writes — this may *improve* performance outright.

Acknowledge early.

A commit can be reported to the client as soon as the *log* is written — the data pages can wait.

So WAL trades **random** writes for **sequential** ones, and trades write *volume* for write *latency*. On spinning disks that was decisive; on SSDs the sequential-write advantage is smaller but the early-acknowledge advantage remains.

The commit path costs **one sequential flush**. That single fact is why the log, and not the data, defines durability.

Improvements to This WAL



COMS4113

Store the LSN of the last write on each data page

pageLSN. Recovery compares it against the log record and skips redos already reflected on the page — avoiding unnecessary work.

Log checkpoint records

Bound how far back recovery must read. Which pages were in memory, and which transactions were live. **Next slide.**

Log the recovery actions themselves (CLRs)

Compensation log records make undo idempotent, so a crash *during* recovery does not redo work already undone.

Ordered / metadata-only logging

Avoids having to record the old value of file data — useful in file systems, where the metadata is what must stay consistent.

Checkpoint Records

Analysis can **start at the last checkpoint** instead of the beginning of the log.

A checkpoint records:


the table of **active transactions**

the table of **dirty pages** in memory

and the **earliest LSN** that might have affected them

Recovery must begin at the **earliest** of the three — the checkpoint alone is not enough, because a transaction or a dirty page may predate it.

Where recovery must start



Transactions in Practice

What a 2026 database actually does

WAL in Production

Recall the observation: *writes across pages may not be atomic*. A **partial** page write breaks redo, because a byte-level record cannot repair a page that is half old and half new.

PostgreSQL

`full_page_writes`

Writes the **whole page image** into the WAL on the first change after a checkpoint, so any torn page can be reconstructed. On by default; `wal_compression` exists to pay back the volume.

MySQL / InnoDB

`doublewrite` buffer

Writes every page **twice** — once to a sequential scratch area, then to its home location. A torn copy is always recoverable from the other.

The durability dial is a configuration option, not a law:

`synchronous_commit = on`

commit waits for the log flush — no committed work is ever lost

`synchronous_commit = off`

commit returns early; a crash may lose **recent commits**, but never corrupts the database

Locking Is Not the Only Way



COMS4113

This lecture taught isolation via **locking**. Most databases you will actually use do it differently.

Locking (2PL)

A reader **blocks** a writer and a writer blocks a reader.
Correct, and the source of most contention.

Still used where conflicts are common — and 2PL remains the model to reason with.

MVCC (Multi Version Concurrency Control)

Keep **multiple versions** of each row. A reader gets a consistent **snapshot** and never blocks; only writer/writer pairs conflict.

The cost moves to storage and to cleaning up old versions.

In **PostgreSQL** today: the default isolation level is **Read Committed**, REPEATABLE READ is snapshot isolation, and SERIALIZABLE is implemented as **Serializable Snapshot Isolation** — snapshots plus conflict detection, **not** two-phase locking.

Consequence for your code: transactions **fail and must be retried** rather than wait. Serialization failures arrive as SQLSTATE **40001**.

Isolation levels: What can go wrong

- **Dirty read:** A transaction reads uncommitted data modified by another concurrent transaction. If the other transaction rolls back, the data read was never actually valid.
- **Non-repeatable read:** A transaction reads the same row twice and gets different values because another transaction modified and committed that row in between the reads.
- **Phantom read:** A transaction re-executes a query returning a set of rows that satisfy a search condition and finds that the set of rows has changed due to another recently committed transaction inserting or deleting rows.
- **Write skew:** Occurs when two concurrent transactions read overlapping sets of data, make local decisions based on what they read, and then update separate data items in a way that violates a global constraint (often seen in snapshot isolation).

Isolation Levels

	Dirty read	Non-repeatable read	Phantom read	Write skew
Read Uncommitted	possible	possible	possible	possible
Read Committed	—	possible	possible	possible
Repeatable Read / snapshot	—	—	—	possible
Serializable	—	—	—	—

Snapshot isolation permits write skew — two transactions each read a state the other is about to invalidate, and both commit. This is what SSI adds detection for.

And note what the table is **not** about: every column here is an **isolation** phenomenon. The **C** in ACID — your application's invariants — appears nowhere, because no isolation level enforces it. Serializable protects your invariant only if your transactions were correct in the first place.

Which Mechanism Buys What

A	C	I	D
Atomicity	Consistency	Isolation	Durability
WAL	you	2PL / MVCC	WAL
undo via old-value; abort is just undo	the DB checks only what you declare	locks, or snapshots plus conflict detection	one sequential flush of the commit record

Both mechanisms exist because the hardware gives us exactly one primitive: a **single atomic page write**. WAL leverages it; locking has nothing to do with it.

Next lecture the disk becomes a *network*, and the same two problems come back much harder.

- We return to the distributed setting to discuss:
 - How to implement distributed transactions in a **sharded** database (for scalability): **atomic commitment** protocols — and 2PC's prepare record is a WAL record, so you have already seen the durable state it depends on.
 - How to implement distributed transactions in a **replicated** database (for fault tolerance): **consensus** protocols.
 - Several **case studies** on leveraging these protocols in practice: Spanner, Chubby, Bigtable.

- **[Mohan-1992]** Mohan, Haderle, Lindsay, Pirahesh & Schwarz. *ARIES: A Transaction Recovery Method Supporting Fine-Granularity Locking and Partial Rollbacks Using Write-Ahead Logging*. ACM TODS **17(1):94–162**, 1992. — the WAL half of this lecture.
- **[Gray-1978]** Jim Gray. *Notes on Data Base Operating Systems*. Advanced Course on Operating Systems, 1978, pp. **393–481**.
- **[Franklin-1997]** Michael J. Franklin. *Concurrency Control and Recovery*. In *The Computer Science and Engineering Handbook*, 1997, pp. **1058–1077**; revised in *Computing Handbook*, 3rd ed., 2014, ch. **12**.
- **[Bernstein-1987]** Bernstein, Hadzilacos & Goodman. *Concurrency Control and Recovery in Database Systems*. Addison-Wesley, 1987 — the standard reference; freely available online.
- **[Adya-2000]** Adya, Liskov & O'Neil. *Generalized Isolation Level Definitions*. ICDE 2000, pp. **67–78**.
- **[Cahill-2009]** Cahill, Röhm & Fekete. *Serializable Isolation for Snapshot Databases*. ACM TODS **34(4):20:1–20:42**, 2009 — the basis of PostgreSQL's SERIALIZABLE.